ACDC Fan

This fan works while internally converting AC power into DC power, providing the superior performance of a DC fan with the flexibility of AC input.

Model Numbering System

Not every combination of the following codes or characters is available. Contact us for an available combination.

9AD	09	01	H	1	2	
Type name	Frame size	Voltage	Speed code	Frame thickness	Sensor specifications	Frame form

Fans with PWM control

9AD	12	01	P	4	H	001	
Type name	Frame size	Voltage	PWM control	Frame thickness	Speed code	Individual customer's spec (2 to 3 digits)	Frame form

Type name	9AD	9ADA	9ADAW	9ADW
Frame size (mm)	09 92×92	12 120×120	16 160×160	57 ø172×150 (sidecut)
Voltage (V)	01 100 to 240			
Speed code	H	M	etc.	
Frame thickness (mm)	1 38	4 25	5 51	
Sensor specifications	001, 003, T03 With a pulse sensor	002, 2, T02 Without a sensor	H, H001, HT01 With a low-speed sensor	
Frame form	Nil Plastic frame: Ribbed frame	1 Plastic frame: Ribless frame		

Centrifugal Fan

9ADT	S	11	P	0	G	001
Type name	Impeller size	Voltage	PWM control	Thickness	Speed code	Individual customer's spec

See category EC AC Centrifugal fans on https://motorsandfans.co.uk/products/cooling-fans/ec-ac-centrifugal-fans/

Bracket-mounted Splash Proof Centrifugal Fan

9ADB1T	S	11	P	0	G	001
Type name	Impeller size	Voltage	PWM control	Thickness	Speed code	Individual customer's spec

Type name	9ADT	9ADW1T	9ADB1T	9ADB1W1T
Impeller size (mm)	S ø225			
Voltage (V)	11 115	23 230		
Thickness (mm)	0 69 min.			
Speed code	G	H	etc.	

How to Read Specifications (ACDC fan)

The following is a sample. See respective product pages for detailed information.

Model no.	Rated voltage [V]	Operating voltage range [V]	Frequency [Hz]	Rated current [A]	Rated input [W]	Rated speed [min⁻¹]	Max. airflow [m³/min]	Max. airflow [CFM]	Max. static pressure [Pa]	Max. static pressure [inchH₂O]	SPL [dB (A)]	Operating temperature [°C]	Expected life [h]
9AD0901H12	100 to 240	90 to 264	50/60	0.08	4.5	3850	1.5	53.0	90	0.36	40	-20 to +75	60000/60°C (90000/40°C)
9AD0901M12				0.06	3.0	3100	1.18	41.7	56	0.22	33		

Rated voltage ····· This is the necessary voltage to drive the fan. Single-phase 100 to 240 VAC are also available.
Operating voltage range ····· The voltage range over which fan operation is guaranteed.
Frequency ····· This is a frequency of alternating current (AC). The frequencies of 50 Hz and 60 Hz are existing in Japan.
Rated current ····· The current when the fan is operating at rated voltage (at free air).
Rated input ····· The power value when the fan is operating at rated voltage (at free air).
Rated speed ····· The speed when the fan is operating at rated voltage (at free air).
Max. airflow ····· The airflow at 0 Pa static pressure when the fan is operating at rated voltage. (Measured using the double chamber method)
Max. static pressure ····· The static pressure at 0 m^3/min airflow when the fan is operating at rated voltage. (Measured using the double chamber method)
SPL ····· A-weighted sound pressure level (SPL) when the fan operates at the rated speed.
For the measurement method, see the Technical Materials section in the catalog.
Operating temperature ····· The temperature range over which fan operation is guaranteed (Non-condensing).
Expected life ····· Service life hours that 90% of bearings will survive without failing when continuously operated at the rated voltage and 60°C temperature. Expected life at 40°C is for reference only.
For more information, please refer to the technical material section.

92×92×25 mm

San Ace 92AD 9AD type

cUL certification is pending for the following models.
9AD0901H4002, 9AD0901M4002, 9AD0901L4002,
9AD0901H4H001, 9AD0901M4H001, 9AD0901L4H001

General Specifications

- Material ..... Frame: Plastic (Flammability: UL 94V-0), Impeller: Plastic (Flammability: UL 94V-0)
- Expected life ..... See the table below. (L10 life: 90% survival rate for continuous operation in free air at 60˚C, rated voltage)
  Expected life at 40°C is for reference only.
- Motor protection function ..... Locked rotor burnout protection
  For details, please refer to p. 616.
- Dielectric strength ..... 50/60 Hz, 2500 VAC, for 1 second (between lead wire conductors and frame)
  50/60 Hz, 1500 VAC, for 1 minute (between input lead wire (L, N) conductors and other lead wire conductors)
- Insulation resistance ..... 10 MΩ min. at 500 VDC
  (between lead wire conductors and frame, between input lead wire (L, N) conductors and other lead wire conductors)
- Sound pressure level (SPL) ..... A-weighted sound pressure level (SPL) at 1 m away from the air inlet.
- Storage temperature ..... -30 to +70˚C (Non-condensing)
- Lead wire ..... (AC power input) L: Orange N: Gray
  (Sensor) Yellow (Control) Brown (GND) Black (For models without sensors, there is no sensor or control wiring.)
- Mass ..... 160 g

Take safety measures not to touch this product (including lead wires) while the power is on.
Please ensure appropriate insulation within the final product because of functional insulation between input leads wire (L, N) and other lead wire conductors.
To display CE mark/UKCA mark on system, refer to p. 621.

Specifications

The models listed below **have ribs and no sensor.** For models without ribs, append "1" to the end of model numbers.

Model no.	Rated voltage [V]	Operating voltage range [V]	Frequency [Hz]	Rated current* [A]	Rated input [W]	Rated speed [min⁻¹]	Max. airflow [m³/min]	Max. airflow [CFM]	Max. static pressure [Pa]	Max. static pressure [inchH₂O]	SPL [dB (A)]	Operating temperature [˚C]	Expected life [h]
9AD0901G4002	100 to 240	90 to 264	50/60	0.06	3.2	3850	1.34	47.3	76	0.305	43	-20 to +70	60000/60˚C (90000/40˚C)
9AD0901H4002				0.04	2.3	3200	1.10	38.8	52	0.208	38		
9AD0901M4002				0.03	1.7	2800	0.97	34.2	40	0.160	34		
9AD0901L4002				0.02	1.1	1900	0.64	22.6	19	0.076	24		

* Rated current ratings are the values at 100 V.

The models listed below **have ribs and a low-speed sensor.** For models without ribs, append "1" to the end of model numbers.

Model no.	Rated voltage [V]	Operating voltage range [V]	Frequency [Hz]	Rated current* [A]	Rated input [W]	Rated speed [min⁻¹]	Max. airflow [m³/min]	Max. airflow [CFM]	Max. static pressure [Pa]	Max. static pressure [inchH₂O]	SPL [dB (A)]	Operating temperature [˚C]	Expected life [h]
9AD0901G4H001	100 to 240	90 to 264	50/60	0.06	3.2	3850	1.34	47.3	76	0.305	43	-20 to +70	60000/60˚C (90000/40˚C)
9AD0901H4H001				0.04	2.3	3200	1.10	38.8	52	0.208	38		
9AD0901M4H001				0.03	1.7	2800	0.97	34.2	40	0.160	34		
9AD0901L4H001				0.02	1.1	1900	0.64	22.6	19	0.076	24		

* Rated current ratings are the values at 100 V.

The models listed below **have ribs and a pulse sensor with PWM control.** For models without ribs, append "1" to the end of model numbers.

Model no.	Rated voltage [V]	Operating voltage range [V]	Frequency [Hz]	PWM duty cycle(1) [%]	Rated current(2) [A]	Rated input [W]	Rated speed [min⁻¹]	Max. airflow [m³/min]	Max. airflow [CFM]	Max. static pressure [Pa]	Max. static pressure [inchH₂O]	SPL [dB (A)]	Operating temperature [˚C]	Expected life [h]
9AD0901P4G001	100 to 240	90 to 264	50/60	100	0.06	3.2	3850	1.34	47.3	76	0.305	43	-20 to +70	60000/60˚C (90000/40˚C)
				30	0.02	0.7	1200	0.42	14.8	8.6	0.034	13		

(1) PWM frequency is 25 kHz. Models without ratings for 0% PWM duty cycle have zero speed at 0%. When control terminal is open, speed is the same as at 0% duty cycle.
(2) Rated current ratings are the values at 100 V.

Airflow - Static Pressure Characteristics

9AD0901G4002
No sensor

Operating voltage range



9AD0901H4002
No sensor

Operating voltage range



9AD0901M4002
No sensor

Operating voltage range



9AD0901L4002
No sensor

Operating voltage range



9AD0901G4H001
With low-speed sensor

Operating voltage range



9AD0901H4H001
With low-speed sensor

Operating voltage range



9AD0901M4H001
With low-speed sensor

Operating voltage range



9AD0901L4H001
With low-speed sensor

Operating voltage range



Airflow - Static Pressure Characteristics / PWM Duty - Speed Characteristics Example

9AD0901P4G001 With pulse sensor with PWM control

PWM duty cycle



PWM duty - Speed characteristics example



Connection Schematic

without Sensor



with Low-speed sensor



with PWM control and pulse sensor



Dimensions (unit: mm) (Ribbed frame with pulse sensor with PWM control)



Reference Dimensions of Mounting Holes and Vent Opening (unit: mm)



Options

Finger guards page: p. 598

Model no.: 109-099E, 109-099H

Resin filter kits page: p. 606

Model no.: 109-1001F13 (13 PPI), 109-1001F20 (20 PPI),
109-1001F30 (30 PPI), 109-1001F40 (40 PPI)

Resin finger guards page: p. 605

Model no.: 109-1001G

92×92×38 mm

San Ace 92AD 9AD type

General Specifications

- Material ..... Frame: Plastic (Flammability: UL 94V-0), Impeller: Plastic (Flammability: UL 94V-0)
- Expected life ..... See the table below. (L10 life: 90% survival rate for continuous operation in free air at 60˚C, rated voltage) Expected life at 40°C is for reference only.
- Motor structure ..... Brushless DC motor
- Motor protection function ..... Locked rotor burnout protection For details, please refer to p. 616.
- Dielectric strength ..... 50/60 Hz, 4000 VAC, for 1 minute (between input terminal and frame) 50/60 Hz, 2500 VAC, for 1 second (between input terminal and sensor output)
- Insulation resistance ..... 10 MΩ min. at 500 VDC (between lead wire conductors and frame)
- Sound pressure level (SPL) ..... A-weighted sound pressure level (SPL) at 1 m away from the air inlet.
- Storage temperature ..... -30 to +75˚C (Non-condensing)
- Mass ..... 250 g

Do not solder wires directly to AC input terminals.

Specifications

The models listed below **have ribs and no sensor.** For models without ribs, append "1" to the end of model numbers.

Model no.	Rated voltage [V]	Operating voltage range [V]	Frequency [Hz]	Rated current* [A]	Rated input [W]	Rated speed [min⁻¹]	Max. airflow [m³/min]	Max. airflow [CFM]	Max. static pressure [Pa]	Max. static pressure [inchH₂O]	SPL [dB (A)]	Operating temperature [˚C]	Expected life [h]
9AD0901H12	100 to 240	90 to 264	50/60	0.08	4.5	3850	1.5	53.0	90	0.36	40	-20 to +75	60000/60˚C (90000/40˚C)
9AD0901M12				0.06	3.0	3100	1.18	41.7	56	0.22	33		

* Rated current ratings are the values at 100 V.

The models listed below **have ribs and a low-speed sensor.** For models without ribs, append "1" to the end of model numbers.

Model no.	Rated voltage [V]	Operating voltage range [V]	Frequency [Hz]	Rated current* [A]	Rated input [W]	Rated speed [min⁻¹]	Max. airflow [m³/min]	Max. airflow [CFM]	Max. static pressure [Pa]	Max. static pressure [inchH₂O]	SPL [dB (A)]	Operating temperature [˚C]	Expected life [h]
9AD0901H1H	100 to 240	90 to 264	50/60	0.08	4.5	3850	1.5	53.0	90	0.36	40	-20 to +75	60000/60˚C (90000/40˚C)
9AD0901M1H				0.06	3.0	3100	1.18	41.7	56	0.22	33		

* Rated current ratings are the values at 100 V.

Set Models

Fan, finger guard, plug cord, screws, etc. can be purchased in one package. For details, please refer to p. 674.

Order no.	Set items					
	Fan (1 pc)	Voltage	Low-speed sensor	Plug cord (1 pc)	Finger guard (1 pc)	Screws with hex nuts (4 pairs)
ST1-9AD0901H12	9AD0901H12	100 to 240 V		489-1635-L10	109-099E	M4×55 mm
ST1-9AD0901M12	9AD0901M12			489-1635-L10	109-099E	
ST1-9AD0901H1H	9AD0901H1H		○	489-1635-L10	109-099E	
ST1-9AD0901M1H	9AD0901M1H		○	489-1635-L10	109-099E	

Airflow - Static Pressure Characteristics

9AD0901H12, 9AD0901H1H



9AD0901M12, 9AD0901M1H



Connection Schematic

without Sensor



with Low-speed sensor



Dimensions (unit: mm) (With ribs)

without Sensor



with Low-speed sensor



Connector: TE Connectivity 171822-2
(Pin1 Sensor output: Yellow Pin2 -: Black)
Contact: TE Connectivity 170262-1

Note: Recommended connectors and contacts are listed below.
Connector: TE Connectivity 172211-2
Contact: TE Connectivity 170376-1

Reference Dimensions of Mounting Holes and Vent Opening (unit: mm)

Inlet side



Outlet side



Options

Finger guards page: p. 598

Model no.: 109-099E, 109-099H

Resin filter kits page: p. 606

Model no.: 109-1001F13 (13PPI), 109-1001F20 (20PPI), 109-1001F30 (30PPI), 109-1001F40 (40PPI)

Sensor extension wiring harness page: p. 611

Model no.: 489-1636

Resin finger guards page: p. 605

Model no.: 109-1001G

Plug cord page: p. 611

Model no.: 489-1635-L10, 489-1635-L21

120×120×25 mm

San Ace 120AD 9AD type

General Specifications

- Material ..... Frame: Plastic (Flammability: UL 94V-0), Impeller: Plastic (Flammability: UL 94V-0)
- Expected life ..... See the table below. (L10 life: 90% survival rate for continuous operation in free air at 60˚C, rated voltage)
  Expected life at 40°C is for reference only.
- Motor protection function ..... Locked rotor burnout protection
  For details, please refer to p. 616.
- Dielectric strength ..... 50/60 Hz, 2500 VAC, for 1 second (between lead wire conductors and frame)
  50/60 Hz, 1500 VAC, for 1 minute (between input lead wire (L, N) conductors and other lead wire conductors)
- Insulation resistance ..... 10 MΩ min. at 500 VDC
  (between lead wire conductors and frame, between input lead wire (L, N) conductors and other lead wire conductors)
- Sound pressure level (SPL) ..... A-weighted sound pressure level (SPL) at 1 m away from the air inlet.
- Storage temperature ..... -30 to +70˚C (Non-condensing)
- Lead wire ..... AC power input L: Orange N: Gray
  Sensor Yellow Control Brown GND Black (For models without sensors, there is no sensor or control wiring.)
- Mass ..... 180 g

Take safety measures not to touch this product (including lead wires) while the power is on.
Please ensure appropriate insulation within the final product because of functional insulation between input leads wire (L, N) and other lead wire conductors.
To display CE mark/UKCA mark on system, refer to p. 621.

Specifications

The models listed below **have ribs and no sensor.** For models without ribs, append "1" to the end of model numbers.

Model no.	Rated voltage [V]	Operating voltage range [V]	Frequency [Hz]	Rated current* [A]	Rated input [W]	Rated speed [min⁻¹]	Max. airflow [m³/min]	Max. airflow [CFM]	Max. static pressure [Pa]	Max. static pressure [inchH₂O]	SPL [dB (A)]	Operating temperature [˚C]	Expected life [h]
9AD1201H4002	100 to 240	90 to 264	50/60	0.06	3.4	3000	2.35	83	62	0.249	40	-20 to +70	60000/60˚C (90000/40˚C)
9AD1201M4002				0.04	1.6	2250	1.76	62	35	0.140	34		
9AD1201L4002				0.03	1.1	1800	1.41	49	22	0.088	26		

* Rated current ratings are the values at 100 V.

The models listed below **have ribs and a low-speed sensor.** For models without ribs, append "1" to the end of model numbers.

Model no.	Rated voltage [V]	Operating voltage range [V]	Frequency [Hz]	Rated current* [A]	Rated input [W]	Rated speed [min⁻¹]	Max. airflow [m³/min]	Max. airflow [CFM]	Max. static pressure [Pa]	Max. static pressure [inchH₂O]	SPL [dB (A)]	Operating temperature [˚C]	Expected life [h]
9AD1201H4H001	100 to 240	90 to 264	50/60	0.06	3.4	3000	2.35	83	62	0.249	40	-20 to +70	60000/60˚C (90000/40˚C)
9AD1201M4H001				0.04	1.6	2250	1.76	62	35	0.140	34		
9AD1201L4H001				0.03	1.1	1800	1.41	49	22	0.088	26		

* Rated current ratings are the values at 100 V.

The models listed below **have ribs and a pulse sensor with PWM control.** For models without ribs, append "1" to the end of model numbers.

Model no.	Rated voltage [V]	Operating voltage range [V]	Frequency [Hz]	PWM duty cycle(1) [%]	Rated current(2) [A]	Rated input [W]	Rated speed [min⁻¹]	Max. airflow [m³/min]	Max. airflow [CFM]	Max. static pressure [Pa]	Max. static pressure [inchH₂O]	SPL [dB (A)]	Operating temperature [˚C]	Expected life [h]
9AD1201P4H001	100 to 240	90 to 264	50/60	100	0.06	3.4	3000	2.35	83	62	0.249	40	-20 to +70	60000/60˚C (90000/40˚C)
				30	0.02	0.7	900	0.7	24.7	6.6	0.03	14		

(1) PWM frequency is 25 kHz. Models without ratings for 0% PWM duty cycle have zero speed at 0%. When control terminal is open, speed is the same as at 0% duty cycle.
(2) Rated current ratings are the values at 100 V.

Airflow - Static Pressure Characteristics

9AD1201H4002
No sensor

Operating voltage range



9AD1201M4002
No sensor

Operating voltage range



9AD1201L4002
No sensor

Operating voltage range



9AD1201H4H001
With low-speed sensor

Operating voltage range



9AD1201M4H001
With low-speed sensor

Operating voltage range



9AD1201L4H001
With low-speed sensor

Operating voltage range



Airflow - Static Pressure Characteristics / PWM Duty - Speed Characteristics Example

9AD1201P4H001
With pulse sensor with PWM control

PWM duty cycle



PWM duty - Speed characteristics example



Connection Schematic

without Sensor



with Low-speed sensor



with PWM control and pulse sensor



Dimensions (unit: mm) (Ribbed frame with pulse sensor with PWM control)



Reference Dimensions of Mounting Holes and Vent Opening (unit: mm)



Options

Finger guards page: p. 599

Model no.: 109-019E, 109-019K

Resin finger guards page: p. 605

Model no.: 109-1000G

Resin filter kits page: p. 606

Model no.: 109-1000F13 (13PPI), 109-1000F20 (20PPI),
109-1000F30 (30PPI), 109-1000F40 (40PPI)

120×120×38 mm

San Ace 120AD 9ADA type

General Specifications

- Material ..... Frame: Plastic (Flammability: UL 94V-0), Impeller: Plastic (Flammability: UL 94V-0)
- Expected life ..... See the table below. (L10 life: 90% survival rate for continuous operation in free air at 60˚C, rated voltage)
  Expected life at 40°C is for reference only.
- Motor protection function ..... Locked rotor burnout protection
  For details, please refer to p. 616.
- Dielectric strength ..... 50/60 Hz, 2500 VAC, for 1 second (between lead wire conductors and frame)
  50/60 Hz, 1500 VAC, for 1 minute (between input lead wire (L, N) conductors and other lead wire conductors)
- Insulation resistance ..... 10 MΩ min. at 500 VDC (between lead wire conductors and frame)
- Sound pressure level (SPL) ..... A-weighted sound pressure level (SPL) at 1 m away from the air inlet.
- Storage temperature ..... -30 to +70˚C (Non-condensing)
- Lead wire ..... AC power input L: Orange N: Gray
  Sensor Yellow Control Brown GND Black
- Mass ..... 340 g

Take safety measures not to touch this product (including lead wires) while the power is on.
Please ensure appropriate insulation within the final product because of functional insulation between input leads wire (L, N) and other lead wire conductors.

Specifications

The models listed below **have ribs and no sensor.** For models without ribs, append "1" to the end of model numbers.

Model no.	Rated voltage [V]	Operating voltage range [V]	Frequency [Hz]	Rated current* [A]	Rated input [W]	Rated speed [min⁻¹]	Max. airflow [m³/min]	Max. airflow [CFM]	Max. static pressure [Pa]	Max. static pressure [inchH₂O]	SPL [dB (A)]	Operating temperature [˚C]	Expected life [h]
9ADA1201G1002	100 to 240	90 to 264	50/60	0.17	9.0	4400	3.9	138	170	0.683	52	-20 to +70	40000/60˚C (70000/40˚C)
9ADA1201H1002				0.13	6.6	3800	3.36	119	128	0.514	48		60000/60˚C (90000/40˚C)

* Rated current ratings are the values at 100 V.

The models listed below **have ribs and a low-speed sensor.** For models without ribs, append "1" to the end of model numbers.

Model no.	Rated voltage [V]	Operating voltage range [V]	Frequency [Hz]	Rated current* [A]	Rated input [W]	Rated speed [min⁻¹]	Max. airflow [m³/min]	Max. airflow [CFM]	Max. static pressure [Pa]	Max. static pressure [inchH₂O]	SPL [dB (A)]	Operating temperature [˚C]	Expected life [h]
9ADA1201G1H001	100 to 240	90 to 264	50/60	0.17	9.0	4400	3.9	138	170	0.683	52	-20 to +70	40000/60˚C (70000/40˚C)

* Rated current ratings are the values at 100 V.

The models listed below **have ribs and a pulse sensor with PWM control.** For models without ribs, append "1" to the end of model numbers.

Model no.	Rated voltage [V]	Operating voltage range [V]	Frequency [Hz]	PWM duty cycle(1) [%]	Rated current(2) [A]	Rated input [W]	Rated speed [min⁻¹]	Max. airflow [m³/min]	Max. airflow [CFM]	Max. static pressure [Pa]	Max. static pressure [inchH₂O]	SPL [dB (A)]	Operating temperature [˚C]	Expected life [h]
9ADA1201P1G001	100 to 240	90 to 264	50/60	100	0.17	9.0	4400	3.9	138	170	0.683	52	-20 to +70	40000/60˚C (70000/40˚C)
				20	0.04	1.4	1050	0.93	32.8	15	0.06	25		

(1) PWM frequency is 25 kHz. Models without ratings for 0% PWM duty cycle have zero speed at 0%. When control terminal is open, speed is the same as at 0% duty cycle.
(2) Rated current ratings are the values at 100 V.

Airflow - Static Pressure Characteristics

9ADA1201G1002 No sensor

Operating voltage range



9ADA1201H1002 No sensor

Operating voltage range



9ADA1201G1H001 With low-speed sensor

Operating voltage range



Airflow - Static Pressure Characteristics / PWM Duty - Speed Characteristics Example

9ADA1201P1G001 With pulse sensor with PWM control

PWM duty cycle



PWM duty - Speed characteristics example



Connection Schematic

without Sensor



with Low-speed sensor



with PWM control and pulse sensor



Dimensions (unit: mm) (Ribbed frame with pulse sensor with PWM control)



Reference Dimensions of Mounting Holes and Vent Opening (unit: mm)

Inlet side



Outlet side



Options

Finger guards page: p. 599

Model no.: 109-019E, 109-019K

Resin filter kits page: p. 606

Model no.: 109-1000F13 (13PPI), 109-1000F20 (20PPI), 109-1000F30 (30PPI), 109-1000F40 (40PPI)

Resin finger guards page: p. 605

Model no.: 109-1000G

120×120×38 mm

San Ace 120AD 9AD type

General Specifications

- Material ..... Frame: Plastic (Flammability: UL 94V-0), Impeller: Plastic (Flammability: UL 94V-1)
- Expected life ..... See the table below. (L10 life: 90% survival rate for continuous operation in free air at 60˚C, rated voltage) Expected life at 40°C is for reference only.
- Motor structure ..... Brushless DC motor
- Motor protection function ..... Locked rotor burnout protection For details, please refer to p. 616.
- Dielectric strength ..... 50/60 Hz, 4000 VAC, for 1 minute (between input terminal and frame) 50/60 Hz, 2500 VAC, for 1 second (between input terminal and sensor output)
- Insulation resistance ..... 10 MΩ min. at 500 VDC (between lead wire conductors and frame)
- Sound pressure level (SPL) ..... A-weighted sound pressure level (SPL) at 1 m away from the air inlet.
- Storage temperature ..... -30 to +75˚C (Non-condensing)
- Mass ..... 290 g

Do not solder wires directly to AC input terminals.

Specifications

The models listed below **have ribs and no sensor.** For models without ribs, append "1" to the end of model numbers.

Model no.	Rated voltage [V]	Operating voltage range [V]	Frequency [Hz]	Rated current* [A]	Rated input [W]	Rated speed [min⁻¹]	Max. airflow [m³/min]	Max. airflow [CFM]	Max. static pressure [Pa]	Max. static pressure [inchH₂O]	SPL [dB (A)]	Operating temperature [˚C]	Expected life [h]
9AD1201H12	100 to 240	90 to 264	50/60	0.08	4.4	3250	3.0	106	84	0.34	42	-20 to +75	60000/60˚C (90000/40˚C)

* Rated current ratings are the values at 100 V.

The models listed below **have ribs and a low-speed sensor.** For models without ribs, append "1" to the end of model numbers.

Model no.	Rated voltage [V]	Operating voltage range [V]	Frequency [Hz]	Rated current* [A]	Rated input [W]	Rated speed [min⁻¹]	Max. airflow [m³/min]	Max. airflow [CFM]	Max. static pressure [Pa]	Max. static pressure [inchH₂O]	SPL [dB (A)]	Operating temperature [˚C]	Expected life [h]
9AD1201H1H	100 to 240	90 to 264	50/60	0.08	4.4	3250	3.0	106	84	0.34	42	-20 to +75	60000/60˚C (90000/40˚C)

* Rated current ratings are the values at 100 V.

Set Models

Fan, finger guard, plug cord, screws, etc. can be purchased in one package. For details, please refer to p. 674.

Order no.	Set items					
	Fan (1 pc)	Voltage	Low-speed sensor	Plug cord (1 pc)	Finger guard (1 pc)	Screws with hex nuts (4 pairs)
ST1-9AD1201H12	9AD1201H12	100 to 240 V		489-1635-L10	109-019E	M4×55 mm
ST1-9AD1201H1H	9AD1201H1H		◯	489-1635-L10	109-019E	

Airflow - Static Pressure Characteristics

9AD1201H12, 9AD1201H1H



Connection Schematic

without Sensor



with Low-speed sensor



Dimensions (unit: mm) (With ribs)

without Sensor



with Low-speed sensor



Connector: TE Connectivity 171822-2
(Pin1 Sensor output: Yellow Pin2 -: Black)
Contact: TE Connectivity 170262-1

Note: Recommended connectors and contacts are listed below.
Connector: TE Connectivity 172211-2
Contact: TE Connectivity 170376-1

Reference Dimensions of Mounting Holes and Vent Opening (unit: mm)



Options

Finger guards page: p. 599

Model no.: 109-019E, 109-019K

Resin filter kits page: p. 606

Model no.: 109-1000F13 (13PPI), 109-1000F20 (20PPI),
109-1000F30 (30PPI), 109-1000F40 (40PPI)

Sensor extension wiring harness page: p. 611

Model no.: 489-1636

Resin finger guards page: p. 605

Model no.: 109-1000G

Plug cord page: p. 611

Model no.: 489-1635-L10, 489-1635-L21

160×160×51 mm

San Ace 160AD 9AD type

General Specifications

- Material ..... Frame: Aluminum (Black coating), Impeller: Plastic (Flammability: UL 94V-0)
- Expected life ..... See the table below. (L10 life: 90% survival rate for continuous operation in free air at 60˚C, rated voltage) Expected life at 40°C is for reference only.
- Motor protection function ..... Locked rotor burnout protection For details, please refer to p. 616.
- Dielectric strength ..... 50/60 Hz, 1500 VAC, for 1 minute (Lead wire model: between lead wire conductors and frame, terminal model: between terminals and frame)
- Insulation resistance ..... 10 MΩ min. at 500 VDC (Lead wire model: between lead wire conductors and frame, terminal model: between terminals and frame)
- Sound pressure level (SPL) ..... A-weighted sound pressure level (SPL) at 1 m away from the air inlet.
- Storage temperature ..... -30 to +70˚C (Non-condensing)
- Lead wire ..... AC power input L: Orange N: Gray Sensor Yellow Control Brown GND Black
- Mass ..... 880 g

To display CE mark/UKCA mark on system, refer to p. 621.

Specifications

The models listed below **have no sensor.**

Model no.	Rated voltage [V]	Operating voltage range [V]	Frequency [Hz]	Rated current(3) [A]	Rated input [W]	Rated speed [min⁻¹]	Max. airflow [m³/min]	Max. airflow [CFM]	Max. static pressure [Pa]	Max. static pressure [inchH₂O]	SPL [dB (A)]	Operating temperature [˚C]	Expected life [h]
9AD1601H5002(1)	100 to 240	90 to 264	50/60	0.46	22	4150	8.2	290	167	0.66	58	-20 to +70	40000/60˚C (70000/40˚C)
9AD1601H5T02(2)				0.46	22	4150	8.2	290	167	0.66	58		

(1) Lead wire model (2) Terminal model (3) Rated current ratings are the values at 100 V.

The models listed below **have a low-speed sensor.**

Model no.	Rated voltage [V]	Operating voltage range [V]	Frequency [Hz]	Rated current(3) [A]	Rated input [W]	Rated speed [min⁻¹]	Max. airflow [m³/min]	Max. airflow [CFM]	Max. static pressure [Pa]	Max. static pressure [inchH₂O]	SPL [dB (A)]	Operating temperature [˚C]	Expected life [h]
9AD1601H5H001(1)	100 to 240	90 to 264	50/60	0.46	22	4150	8.2	290	167	0.66	58	-20 to +70	40000/60˚C (70000/40˚C)
9AD1601H5HT01(2)				0.46	22	4150	8.2	290	167	0.66	58		

(1) Lead wire model (2) Terminal model (3) Rated current ratings are the values at 100 V.

The models listed below **have a pulse sensor with PWM control.**

Model no.	Rated voltage [V]	Operating voltage range [V]	Frequency [Hz]	PWM duty cycle(3) [%]	Rated current(4) [A]	Rated input [W]	Rated speed [min⁻¹]	Max. airflow [m³/min]	Max. airflow [CFM]	Max. static pressure [Pa]	Max. static pressure [inchH₂O]	SPL [dB (A)]	Operating temperature [˚C]	Expected life [h]
9AD1601P5H003(1)	100 to 240	90 to 264	50/60	100	0.46	22	4150	8.2	290	167	0.66	58	-20 to +70	40000/60˚C (70000/40˚C)
				0	0.10	4.0	1500	3.07	108	44	0.17	31		
9AD1601P5HT03(2)				100	0.46	22	4150	8.2	290	167	0.66	58		
				0	0.10	4.0	1500	3.07	108	44	0.17	31		

(1) Lead wire model (2) Terminal model
(3) PWM frequency is 25 kHz. Models without ratings for 0% PWM duty cycle have zero speed at 0%. When control terminal is open, speed is the same as at 0% duty cycle.
(4) Rated current ratings are the values at 100 V.

Airflow - Static Pressure Characteristics

9AD1601H5002, 9AD1601H5T02
No sensor

Operating voltage range



9AD1601H5H001, 9AD1601H5HT01
With low-speed sensor

Operating voltage range



Airflow - Static Pressure Characteristics / PWM Duty - Speed Characteristics Example

9AD1601P5H003, 9AD1601P5HT03 With pulse sensor with PWM control

PWM duty cycle



PWM duty - Speed characteristics example



Connection Schematic

without Sensor



with Low-speed sensor



with PWM control and pulse sensor



Dimensions (unit: mm) (With pulse sensor with PWM control)

Lead wire model



Terminal model



A Connector contact



Pin assignment
Connector (Model no.:TE Connectivity: 1-172160-9)

Pin No.	Function	Type
1	L	AC
2	No connection	-
3	N	AC
4	PWM	DC
5	GND	DC
6	Sensor	DC

Reference Dimensions of Mounting Holes and Vent Opening (unit: mm)

Inlet side, Outlet side



Options

Finger guards page: p. 599

Model no.: 109-619E, 109-619H

Terminal model wiring harness page: p. 611

Compatible with a fan without sensor.
Model no.: 489-1648, 489-1651

Compatible with a fan with low-speed sensor, and a fan with pulse sensor and PWM control.
Model no.: 489-1647, 489-1650

ø172×150×51 mm

San Ace 172AD 9AD type

Sidecut type

General Specifications

- Material ..... Frame: Aluminum (Black coating), Impeller: Plastic (Flammability: UL 94V-0)
- Expected life ..... See the table below. (L10 life: 90% survival rate for continuous operation in free air at 60˚C, rated voltage) Expected life at 40°C is for reference only.
- Motor protection function ..... Locked rotor burnout protection For details, please refer to p. 616.
- Dielectric strength ..... 50/60 Hz, 1500 VAC, for 1 minute (Lead wire model: between lead wire conductors and frame, terminal model: between terminals and frame)
- Insulation resistance ..... 10 MΩ min. at 500 VDC (Lead wire model: between lead wire conductors and frame, terminal model: between terminals and frame)
- Sound pressure level (SPL) ..... A-weighted sound pressure level (SPL) at 1 m away from the air inlet.
- Storage temperature ..... -30 to +70˚C (Non-condensing)
- Lead wire ..... AC power input L: Orange N: Gray Sensor Yellow Control Brown GND Black
- Mass ..... 750 g

To display CE mark/UKCA mark on system, refer to p. 621.

Specifications

The models listed below **have no sensor.**

Model no.	Rated voltage [V]	Operating voltage range [V]	Frequency [Hz]	Rated current(3) [A]	Rated input [W]	Rated speed [min⁻¹]	Max. airflow [m³/min]	Max. airflow [CFM]	Max. static pressure [Pa]	Max. static pressure [inchH₂O]	SPL [dB (A)]	Operating temperature [˚C]	Expected life [h]
9AD5701H5002(1)	100 to 240	90 to 264	50/60	0.3	17	3800	6.7	236	195	0.78	54	-20 to +70	40000/60˚C (70000/40˚C)
9AD5701H5T02(2)				0.3	17	3800	6.7	236	195	0.78	54		

(1) Lead wire model (2) Terminal model (3) Rated current ratings are the values at 100 V.

The models listed below **have a low-speed sensor.**

Model no.	Rated voltage [V]	Operating voltage range [V]	Frequency [Hz]	Rated current(3) [A]	Rated input [W]	Rated speed [min⁻¹]	Max. airflow [m³/min]	Max. airflow [CFM]	Max. static pressure [Pa]	Max. static pressure [inchH₂O]	SPL [dB (A)]	Operating temperature [˚C]	Expected life [h]
9AD5701H5H001(1)	100 to 240	90 to 264	50/60	0.3	17	3800	6.7	236	195	0.78	54	-20 to +70	40000/60˚C (70000/40˚C)
9AD5701H5HT01(2)				0.3	17	3800	6.7	236	195	0.78	54		

(1) Lead wire model (2) Terminal model (3) Rated current ratings are the values at 100 V.

The models listed below **have a pulse sensor with PWM control.**

Model no.	Rated voltage [V]	Operating voltage range [V]	Frequency [Hz]	PWM duty cycle(3) [%]	Rated current(4) [A]	Rated input [W]	Rated speed [min⁻¹]	Max. airflow [m³/min]	Max. airflow [CFM]	Max. static pressure [Pa]	Max. static pressure [inchH₂O]	SPL [dB (A)]	Operating temperature [˚C]	Expected life [h]
9AD5701P5H003(1)	100 to 240	90 to 264	50/60	100	0.3	17	3800	6.7	236	195	0.78	54	-20 to +70	40000/60˚C (70000/40˚C)
				0	0.08	3.2	1500	2.64	93	40	0.16	31		
9AD5701P5HT03(2)				100	0.3	17	3800	6.7	236	195	0.78	54		
				0	0.08	3.2	1500	2.64	93	40	0.16	31		

(1) Lead wire model (2) Terminal model
(3) PWM frequency is 25 kHz. Models without ratings for 0% PWM duty cycle have zero speed at 0%. When control terminal is open, speed is the same as at 0% duty cycle.
(4) Rated current ratings are the values at 100 V.

Airflow - Static Pressure Characteristics

9AD5701H5002, 9AD5701H5T02
No sensor

Operating voltage range



9AD5701H5H001, 9AD5701H5HT01
With low-speed sensor

Operating voltage range



Airflow - Static Pressure Characteristics / PWM Duty - Speed Characteristics Example

9AD5701P5H003, 9AD5701P5HT03 With pulse sensor with PWM control

PWM duty cycle



PWM duty - Speed characteristics example



Connection Schematic

without Sensor



with Low-speed sensor



with PWM control and pulse sensor



Dimensions (unit: mm) (With pulse sensor with PWM control)

Lead wire model



Terminal model



A Connector contact



Pin assignment
Connector (Model no.:TE Connectivity: 1-172160-9)

Pin No.	Function	Type
1	L	AC
2	No connection	-
3	N	AC
4	PWM	DC
5	GND	DC
6	Sensor	DC

Reference Dimensions of Mounting Holes and Vent Opening (unit: mm)

Inlet side, Outlet side



Options

Finger guards page: p. 600

Model no.: 109-1155, 109-1155H

Terminal model wiring harness page: p. 611

Compatible with a fan without sensor.
Model no.: 489-1648, 489-1651

Compatible with a fan with low-speed sensor, and a fan with pulse sensor and PWM control.
Model no.: 489-1647, 489-1650